

DECLARATION OF PERFORMANCE

No. 132CPR2013-07-02 LV

1. Unique identification code of the product-type:

Decorative masonry and grouting mortar CMM

2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as specified by manufacturer:

General purpose masonry for interior or exterior use

3. Manufacturer name, registered trade name or registered trade mark and contact address:

SIA "SAKRET"

„Ritvari”, Rumbula, Stopiņu parish., Ropazu district, Latvia, LV-2121

4. Name and contact address of authorized representative: **not applicable**

5. System/s of AVCP: **system 4**

6. Harmonised standard for construction product: **LVS EN 998-2:2020**


7. Declared performance/s:

Essential characteristic	Performance	Harmonised technical specification
Compressive strength:	M5	EN 998-2
Water absorption coefficient:	$\leq 0,3 \text{ kg}/(\text{m}^2 \cdot \text{min}^{0,5})$	
Water vapour permeability coefficient (μ):	15/35	
Shear strength (table value):	$\geq 0,15 \text{ N}/\text{mm}^2$	
Contents of chloride:	$< 0,1\%$	
Durability (freeze/thaw resistance):	F35	
Thermal conductivity $\lambda_{10, \text{dry}}$ (table value):	$\leq 0,83 \text{ W}/(\text{mK}) \text{ P}=50\%$ $\leq 0,93 \text{ W}/(\text{mK}) \text{ P}=90\%$	
Reaction to fire:	class A1 (incombustible)	
Dangerous substance	See MSDS	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **not applicable**
The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

SIA "SAKRET"
Chief Technologist
Baiba Migliniece


At Rumbula on 31.01.2022